



Specifications

- Perfect device for unattended fogging with automatic shut-off
- Rooms up to 500 m³
- Nozzle 2 x W03
- max. flow compressed air 100 - 400 l/min
- max. pressure compressed air 8 bar
- Compressed air connection: plug-in nipple NW 7.2 mm
- Manual switching: 1 nozzle – off – 2 nozzles
- IP45 degree of protection
- 230 V AC 50 Hz, approx. 200 W
- Electrical connection: 3 m power cable with Schuko plug CEE 7/7
- Capacity of the central container: 10 l
- Automatic shutdown by means of a level sensor
- Dimensions: L=56 cm x W=27 cm x H=57 cm
- Weight empty: approx. 9.8 kg
- Droplet spectrum: Ø 6–16 µm


Performance data

Pressure	Effective delivery quantity Compressed air	Average throughput (depending on dosing nozzle and orifice insert)			Range of the fog in space
		Dry fog for	Medium fog for	Wet fog for	
		<ul style="list-style-type: none"> • Plant protection • Remedy • Pest control • Disinfection 	<ul style="list-style-type: none"> • Desinfektion 	<ul style="list-style-type: none"> • Befeuchtung 	
3 bar	200 l/min	2 bis 4 l/h	bis 10 l/h	bis 16 l/h	bis 36 m
6 bar	400 l/min	4 bis 6 l/h	bis 16 l/h	bis 24 l/h	bis 46 m