



 **Specifications**

- Perfect device for fogging large rooms up to 7,500 m³
- Fan to increase the range
- Dimensions: L=125 cm x W=75 cm x H=110 cm
- Weight: approx. 72 kg
- 230 V AC 50 Hz, approx. 400 W
- Electrical connection: 3 m power cable with Schuko plug CEE 7/7
- Compressed air connection: GEKA 1/2"
- Max. pressure compressed air 8 bar
- Max. flow compressed air: 3.2 m³/min
- Medium tank capacity: 100 l with tank flush
- Fan, 0.4 kW, 5-stage air rate setting up to 7,760 m³/h
- Adjustable average dosage by means of a flow meter and diaphragm pump: up to 60 l/h
- Nozzles can be switched in groups: 1 – 3 – 4

 **Performance data**

Number of nozzles	Pressure	Effective delivery quantity Compressed air	Medium throughput			Range of the fog in space
			Dry fog for	Medium fog for	Wet fog for	
			<ul style="list-style-type: none"> • Plant protection • Remedy • Pest control • Disinfection 	<ul style="list-style-type: none"> • Disinfection 	<ul style="list-style-type: none"> • Humidification 	
1 x W06	3 bar	400 l/min	bis 5 l/h	bis 12 l/h	bis 24 l/h	Nozzle up to 45 m with fan up to 100 m
	6 bar	800 l/min	bis 10 l/h	bis 24 l/h	bis 48 l/h	
4 x W06	3 bar	1.600 l/min	bis 13 l/h	bis 26 l/h	bis 50 l/h	Nozzle up to 55 m with fan up to 100 m
	6 bar	3.200 l/min	bis 28 l/h	bis 42 l/h	bis 60 l/h	