



## Specifications

- Perfect device for fogging large rooms up to 15,000 m<sup>3</sup>
- Fan to increase the range
- Dimensions: L=125 cm x W=75 cm x H=110 cm
- Weight: approx. 72 kg
- 230 V AC 50 Hz, approx. 400 W
- Electrical connection: 3 m power cable with Schuko plug CEE 7/7
- Compressed air connection: GEKA 1/2"
- Max. pressure compressed air 8 bar
- Max. flow compressed air: 5.6 m<sup>3</sup>/min
- Medium tank capacity: 100 l with tank flush
- Fan, 0.4 kW, 5-stage air rate setting up to 7,760 m<sup>3</sup>/h
- Adjustable average dosage by means of a flow meter and diaphragm pump: up to 60 l/h
- Nozzles can be switched in groups: 1 – 3 – 4

## Performance data

Number of nozzles	Pressure	Effective delivery quantity Compressed air	Medium throughput			Range of the fog in space
			dry fog for	medium fog for	wet fog for	
			<ul style="list-style-type: none"> <li>• Plant protection</li> <li>• Remedy</li> <li>• Pest control</li> <li>• Disinfection</li> </ul>	<ul style="list-style-type: none"> <li>• Disinfection</li> </ul>	<ul style="list-style-type: none"> <li>• Humidification</li> </ul>	
1 x W06	3 bar	400 l/min	bis 5 l/h	bis 12 l/h	bis 24 l/h	Nozzle up to 45 m with fan up to 100 m
	6 bar	800 l/min	bis 10 l/h	bis 24 l/h	bis 48 l/h	
7 x W06	3 bar	2.800 l/min	bis 15 l/h	bis 30 l/h	bis 60 l/h	Nozzle up to 55 m with fan up to 100 m
	6 bar	5.600 l/min	bis 30 l/h	bis 50 l/h	bis 60 l/h	